



## 3415MZ0

Right Angle Light

### The intrinsically safe work light packed with features and a magnet

The 3415MZ0 is the ultimate ATEX safety-certified compact work light. The Zone 0 (Category 1) certification provides the security needed for almost all hazardous locations. Driven by only 3AA batteries, the 3415MZ0 is equipped with both a spot and flood LED. This allows for close up as well as distant lighting needs. It is engineered to run on either or both LEDs. The articulating head and built in clip provide hands free and handheld options so you can direct the light wherever it is needed. The 3415MZ0 includes an integrated magnet expanding its hands free applications, truly a multi-task torch designed to bring great value to your lighting needs.

- Articulating Light Head
- Attached clip with integrated magnet
- Security Lanyard
- ATEX Zone 0 (Category 1) certified
- Split ring installed
- 2 modes: spot, flashing



## DIMENSIONS

|               |                 |
|---------------|-----------------|
| <b>Length</b> | 7.44" (18.9 cm) |
|---------------|-----------------|

## MATERIALS

|                                |   |
|--------------------------------|---|
| <b>Body</b>                    | Anti-static Impact Modified PC/PBT                      |
| <b>O-Ring</b>                  | NBR   |
| <b>Lens</b>                    | Anti-static coated Polycarbonate (PC)                   |
| <b>Shroud</b>                  | Anti-static Impact Modified PC/PBT                      |
| <b>Clip</b>                    | Anti-static Impact Modified PC/PBT                      |
| <b>Contact Spring Retainer</b> | Stainless Steel / Phosphore Bronze / Brass Nickel Plate |

## COLOURS

|  |
|--|
|  High Visibility Yellow |
|--|

## LIGHT SPECS

|                            |     |
|----------------------------|-----|
| <b>Lamp Type</b>           | LED |
| <b>Lamp Secondary Type</b> | LED |

## POWER

|                         |          |
|-------------------------|----------|
| <b>Battery Size</b>     | AA       |
| <b>Battery Type</b>     | Alkaline |
| <b>Battery Quantity</b> | 3        |
| <b>Volts</b>            | 4.5v     |

## WEIGHT

|                                 |                 |
|---------------------------------|-----------------|
| <b>Weight With Batteries</b>    | 9.6 oz (272 gr) |
| <b>Weight Without Batteries</b> | 7.1 oz (201 gr) |

SWITCH

|             |                 |
|-------------|-----------------|
| Switch Type | Push Button     |
| Light Modes | High / Flashing |

CERTIFICATIONS

|             |
|-------------|
| ATEX Zone 0 |
| IECEX ia    |

| FL1 STANDARD  | SPOT / FLOOD  | FLOOD         | SPOT          |
|---|---------------|---------------|---------------|
|    | 329<br>LUMENS | 174<br>LUMENS | 185<br>LUMENS |
|    | 6h 0mins      | 15h 0mins     | 14h 0mins     |
|   | 133m          | 38m           | 134m          |
|  | 4425cd        | 354cd         | 4517cd        |
|  | IPX8 (1m)     |               |               |

**Peli**  
c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999  
[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)

Document created on 05-11-24