



## iM3200

### Storm

#### Long Case

The Peli™ Storm Case™ has the same legendary DNA as our Peli Protector Case, with one primary difference: A unique Press and Pull latch that locks automatically, but open with a light touch. Guaranteed for life, the Peli Storm case is made in the USA and engineered using the finest components.

- Six Press & Pull Latches
- Two Padlockable Hasps
- Two Double-layered, Soft-grip Handles
- Vortex™ Valve
- Powerful Hinges
- O-ring seal
- Lightweight Strong HPX® Resin



## CONFIGURATIONS



**iM3200**  
Standard



**iM3200-X0000**  
No Foam



**iM3200-X0001**  
With Foam

## DIMENSIONS

|                              |                                                |
|------------------------------|------------------------------------------------|
| <b>Interior (L×W×D)</b>      | 44.00 x 14.00" x 6.00 (111.8 x 35.6 x 15.2 cm) |
| <b>Exterior (L×W×D)</b>      | 47.20 x 16.50" x 6.70 (119.9 x 41.9 x 17 cm)   |
| <b>Lid Depth</b>             | 2.00" (5.1 cm)                                 |
| <b>Bottom Depth</b>          | 4.00" (10.2 cm)                                |
| <b>Total Depth</b>           | 6" (15.2 cm)                                   |
| <b>Int Volume</b>            | 2.14 ft <sup>3</sup> (0.061 m <sup>3</sup> )   |
| <b>Padlock Hole Diameter</b> | 0.38" (1 cm)                                   |

## MATERIALS

|                         |                                              |
|-------------------------|----------------------------------------------|
| <b>Body</b>             | Injection Molded HPX™ high performance resin |
| <b>Latch</b>            | Valox - Polybutylene Terephthalate (PBT)     |
| <b>Latch (Alt)</b>      | Xenoy - Polyester/Polycarbonate blend        |
| <b>O-Ring</b>           | EPDM                                         |
| <b>Pins</b>             | Stainless Steel                              |
| <b>Pins (Alt)</b>       | Aluminum                                     |
| <b>Foam</b>             | 1.3/1.35 polyester                           |
| <b>Purge Body</b>       | Valox - Polybutylene Terephthalate (PBT)     |
| <b>Purge Body (Alt)</b> | Xenoy - Polyester/Polycarbonate blend        |
| <b>Purge Vent</b>       | Gortex membrane                              |

## COLOURS

■ Black

■ OD Green

## WEIGHT

|                           |                      |
|---------------------------|----------------------|
| <b>Weight With Foam</b>   | 21.10 lbs (9.6 kg)   |
| <b>Weight Empty</b>       | 17.70 lbs (8 kg)     |
| <b>Buoyancy</b>           | 136.09 lbs (61.7 kg) |
| <b>Master Pack Weight</b> | 19.70 lbs (8.9 kg)   |

## TEMPERATURE

|                            |                  |
|----------------------------|------------------|
| <b>Minimum Temperature</b> | -20°F (-28.9 °C) |
| <b>Maximum Temperature</b> | 140°F (60 °C)    |


## CERTIFICATIONS

**IP67**

## OTHER

|                    |     |
|--------------------|-----|
| <b>Master Pack</b> | 1   |
| <b>Military</b>    | yes |

## ACCESSORIES



**iM3200-FOAM**  
4 pc. Replacement Foam Set



**iM-STRAP-S-VER2**  
Padded Shoulder Strap



**iM-LIDSTAY**  
Lid Stay



**1506TSA**  
TSA Lock



**1500D**  
Desiccant Silica Gel

### Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999  
[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)

Document created on 05-19-24